

ARCHITECTURAL PRODUCTS COMPANY

AP SNAP-TIGHT COPING

1290 AVIATION BLVD. SUITE 200 P.O. BOX 630 HEBRON, KY 41048

KY (859) 689-2210 OUT STATE (800) 837-1001 FAX (859) 689-2215 FORMED ALUM. OR GALV. SNAP-TIGHT COPING W/ 8" QUANTITY CONCEALED JOINT COVER PLATES (10'0" O.C.) 18 GA. GALV. ANCHOR PLATEASSEMBLY(5'0" O.C.) FT. TOTAL PERIMETER __ PCS STOCK @ 10'0" PCS STD. O.S. CORNER _PCS STD. I.S. CORNER _PCS SPEC. CORNER (ATTACH SKETCHES) PCS END CAP - L SPECIFY INSIDE DIMENSION OF SYSTEM _PCS ENDCAP - R PCS END TERM - L **AP SNAP-TIGHT COPING** PCS END TERM - R 3/8"X I/I6" BUTYL WATER BARRIER STRIPS EACH SIDE OF JOINT (FIELD APPLY) CONCEALED ALUM. JOINT COVER FORMED ALUM. SNAP-TIGHT COPING (8" WIDE) 10'0" O.C. . 18 GA. GALV. ANCHOR PLATE ASSEMBLY EASTENED SECURELY TO THE WALL AT 5'0" O.C. COPING ISOMETRIC WELDED CORNERS DECODIDATION

DETAIL ——— P	RCH'L REF	DESC	ZKIPTION			
SIZE	GAUGE	MATERIAL		FINISH		
A= B= C=	☐ .050 ☐ .063 ☐ .080 ☐ 24 GA ☐ 22 GA	<u>=</u>	STEEL LESS STEEL ———	K) CL BF BL	 MILL FINISH KYNAR 500 CLEAR ANODIZED BRONZE ANODIZED BLACK ANODIZED 	
TRANSMITTAL CUSTOMER APPR						
REQUEST FOR QUOTATION REQUEST FOR INFORMATION SUBMIT AS QUOTATION CONFIRMING TELCON SUBMIT FOR APPROVAL FOR YOUR FILES			APPROVED FOR FABRICATION APPROVED WITH CHANGES DISAPPROVED, RESUBMIT AUTHORIZED CUSTOMER SIGNATURE			
BY	DATE			-	TITLE	DATE
JOB NAME					JOB #	
LOCATION					SHEET	OF
CUSTOMER					BY	
REPRESENTATIVE					DATE	
ARCHITECT						